



Easy application. Reliable Performance. Lower Cost.

QuietSeal Pro is a high performing, non-hardening acoustical sealant used to maintain optimum acoustic performance of the Quiet Soundproofing System. QuietSeal Pro stays soft to prevent cracking and reduce sound transmission. Apply QuietSeal Pro around perimeters of the walls, ceilings and wall partitions, junction boxes and any small penetrations to stop noise leakage in your assembly. It's easy to use and offers a hassle free clean up – just use soap and water. Choose QuietSeal Pro for fast application, maximum performance, and reliable results when used as part of the Quiet Soundproofing System.

QuietSeal Pro Benefits:

- Optimizes soundproofing performance
- Easy application
- Hassle free clean up
- Stays soft for high acoustic performance
- Environmentally friendly: water-based, low VOC and low odor
- Exceeds ASTM C834 standards

Product Specifications:

Model:	QuietSeal Pro
Color:	Light Blue
Coverage:	86 ft.
Weight:	3 lbs/tube
Volume shrinkage:	18.4%
Cure time:	24-48 hours
Storage temp:	40°-100°F



Product Application

Ensure surfaces are clean and dry prior to application. Apply a 1/8" - 1/4" bead of QuietSeal Pro to:

1. The perimeter of walls, ceilings, floors, and any penetrations
2. Any wallboard seam that is not backed by a stud
3. Make sure the gap is completely filled with QuietSeal Pro for best soundproofing results

The information contained in this document is for general information purposes only. Features and specifications are subject to change. Construction practices have an influence on final STC ratings. Serious Energy cannot guarantee actual STC ratings. Flanking sound patterns, the integrity of the wall, and floor and ceiling construction are important factors in effective sound control.